

Ambienti

AKF 5.25LCRS

In-Wall 2-way LCRS

5-1/4" Rectangular Frameless

Frequency Response: 45Hz - 21kHz $\pm$ 3 dB

Power Handling: 50 watts nom. 100 max.

Sensitivity: 90dB 1 watt / 1 meter

Tweeter: 1" Teton® soft dome pivoting

Impedance: 8 ohms nominal

Overall Dimensions: 9" x 15-3/4"

Cut-Out: 7-15/16" x 14-7/16" x 3-1/4" D



Rear View




Side View



Features:

- Woven woofers made from genuine DuPont™ Kevlar®
- Magnetic, frameless, vibration-free, all-weather grille
- Industry leading superior clamp-ring mounting system
- High-grade crossovers with polyswitch overdrive protection
- Baffle mounted mid & high frequency acoustic compensation / EQ switches
- IR knockouts
- Mounts vertically or horizontally
- Sold and shipped individually
- Phase plug for high power handling
- New linear high-excursion design
- High temperature Polyimide voice coils

Optional Pre-Construction Bracket



Angstrom
LOUDSPEAKERS

DuPont™ and Kevlar® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company



Rev. A

Angstrom Loudspeakers MC

391 Marwood Drive, Unit 6, Oshawa, Ontario L1H 7P8 • TEL: 416-988-8806

www.AngstromLoudspeakers.com

View all
of our
Models:

